

DTIC FILE COPY

④

AD-A204 456

**SCALING PROPERTIES OF
COARSE-CODED SYMBOL MEMORIES**

Technical Report AIP-10

Ronald Rosenfeld and David S. Touretzky

Computer Science Department
Carnegie-Mellon University
Pittsburgh, PA 15213

**The Artificial Intelligence
and Psychology Project**

Departments of
Computer Science and Psychology
Carnegie Mellon University

Learning Research and Development Center
University of Pittsburgh

DTIC
ELECTE
DEC 28 1988
S D
cy D

Approved for public release; distribution unlimited.

88 12 28 051

~~4~~
4

SCALING PROPERTIES OF COARSE-CODED SYMBOL MEMORIES

Technical Report AIP-10

Ronald Rosenfeld and David S. Touretzky

Computer Science Department
Carnegie-Mellon University
Pittsburgh, PA 15213

29 September 1987

DTIC
S DEC 28 1988 D
CD

This research was supported by the Computer Sciences Division, Office of Naval Research and DARPA under Contract Number N00014-86-K-0678. Reproduction in whole or in part is permitted for purposes of the United States Government. Approved for public release; distribution unlimited.

2
QUALITY
INSPECTED

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Date	
Distribution	
Comments	
A-1	

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; Distribution unlimited		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
4. PERFORMING ORGANIZATION REPORT NUMBER(S) A I P - 10			7a. NAME OF MONITORING ORGANIZATION Computer Sciences Division Office of Naval Research (Code 1103)		
6a. NAME OF PERFORMING ORGANIZATION Carnegie-Mellon University			7b. ADDRESS (City, State, and ZIP Code) 800 N. Quincy Street Arlington, Virginia 22217-5000		
6b. OFFICE SYMBOL (if applicable)			9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER N00014-86-K-0678		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION Same as Monitoring Organization			10. SOURCE OF FUNDING NUMBERS p400005ub201; 7-4-86		
8b. OFFICE SYMBOL (if applicable)			PROGRAM ELEMENT NO N/A	PROJECT NO. N/A	TASK NO. N/A
8c. ADDRESS (City, State, and ZIP Code)			WORK UNIT ACCESSION NO N/A		
11. TITLE (Include Security Classification) Scaling Properties of Coarse-Coded Symbol Memories					
12. PERSONAL AUTHOR(S) R. Rosenfeld and D.S. Touretzky					
13a. TYPE OF REPORT Technical		13b. TIME COVERED FROM 86Sept15 to 91Sept14		14. DATE OF REPORT (Year, Month, Day) 87 September 29	
15. PAGE COUNT 4					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Artificial Intelligence, Machine Learning, Connectionism, Short Term Memory, distributed representation		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>Coarse coded memories have appeared in several neural network symbol processing models, such as Touretzky and Hinton's distributed connectionist production system DCPS, Touretzky's distributed implementation of Lisp S-expressions on a Boltzmann machine, and St. John and McClelland's PDP model of case role defaults. In order to determine how these models would scale, one must first have some understanding of the mathematics of coarse coded representations. For example, the working memory of DCPS, which stores triples of symbols and consists of 2,000 units, can hold roughly 20 items at a time out of a 15,625-symbol alphabet. How would DCPS scale if the alphabet size were raised to 50,000? With the current alphabet size, how many units would have to be added simply to double the working memory capacity to 40 triples? We present some analytical results related to these questions. (12F) —</p> <p>The authors</p>					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION		
22a. NAME OF RESPONSIBLE INDIVIDUAL Dr. Alan L. Meyrowitz			22b. TELEPHONE (Include Area Code) (202) 696-4302		22c. OFFICE SYMBOL N00014

Scaling Properties of Coarse-Coded Symbol Memories

Ronald Rosenfeld
David S. Touretzky

Computer Science Department
Carnegie Mellon University
Pittsburgh, PA 15213

Summary

Coarse coded memories have appeared in several neural network symbol processing models, such as Touretzky and Hinton's distributed connectionist production system DCPS [6,7], Touretzky's distributed implementation of Lisp S-expressions on a Boltzmann machine, BoltzCONS [8,9], and St. John and McClelland's PDP model of case role defaults [4]. In order to determine how these models would scale, one must first have some understanding of the mathematics of coarse coded representations. For example, the working memory of DCPS, which stores triples of symbols, consists of 2,000 units, can hold roughly 20 items at a time out of a 15,625-symbol alphabet. How would DCPS scale if the alphabet size were raised to 50,000? With the current alphabet size, how many units would have to be added simply to double the working memory capacity to 40 triples? We present some analytical results related to these questions.

A coarse coded symbol memory in its most general form is defined by two parameters: the alphabet size α and the number of units, N . Each unit has a "receptive field" containing some subset of the alphabet. Symbols are stored in memory by turning on all the units in whose receptive field they fall. Thus, symbols are represented as distributed patterns of activity, and the units are said to be "coarsely tuned" because each participates in the representation of more than one symbol. However, our units' receptive fields are not restricted to contiguous subregions of a multidimensional feature space as are the "value units" of [1,2,3,5]. They are instead random subsets of a one-dimensional symbol space.

A symbol is deemed present if all its receptors are active (our analysis easily generalizes to a weaker criterion). As items are added, "ghost" symbols eventually appear; these are symbols which were not stored, but appear because all their receptors are shared with symbols that were stored. The capacity or "span" of a memory is the number of symbols k that can be stored before ghosts appear. (A localist representation, where $k = \alpha = N$, is very inefficient for sparse memories with a large alphabet.)

In this analysis we assume that symbols have a uniform receptor set size L , and that each of the

α symbols is assigned a random L -subset of the N units making up the memory. The probability of a ghost appearing after k symbols have been stored is given by Equation 1:

$$P_{\text{ghost}}(N, L, k, \alpha) = 1 - \sum_{c=0}^N T_{N,L}(k, c) \cdot \left[1 - \frac{\binom{c}{L}}{\binom{N}{L}} \right]^{\alpha-k} \quad (1)$$

$T_{N,L}(k, c)$ is the probability that exactly c units will be active after k symbols have been stored. It is defined by Equation 2:

$$T_{N,L}(k, c) = \sum_{a=0}^L T(k-1, c-a) \cdot \frac{\binom{N-(c-a)}{a} \binom{c-a}{L-a}}{\binom{N}{L}} \quad (2)$$

$$T_{N,L}(0, c) = 0 \quad \text{for all } c.$$

The optimal pattern size with respect to N , k , and α can be determined by binary search on Equation 1. However, this may be expensive for large N . A good initial estimate is the L that maximizes the following expression:

$$\frac{\binom{N \cdot [1 - (1-L/N)^k]}{L}}{\binom{N}{L}} \quad (3)$$

We have constructed coarse coded memories of various sizes and measured their capacities experimentally. The results show good agreement with the predicted values.

We present graphs of the relationships between N , k , α , and P_{ghost} for optimum pattern sizes, as determined by Equation 1. A representative graph is shown in Figure 1. The results show an exponential relationship between α and N/k . Thus, for a fixed alphabet size, the span is proportional to the number of units. For $P_{\text{ghost}} = 0.01$ the relationship is:

$$\alpha = e^{[0.468 \frac{N}{k} - 4.76]} \quad (4)$$

We compare the capacity obtained using our probabilistic, random receptive fields approach with that of two other approaches which guarantee a specified span: a binary coding scheme, and an approach where the overlap between any two patterns is bounded by $\lfloor (L-1)/k \rfloor$.

References

- [1] Ballard, D. H. (1986) Cortical connections and parallel processing: structure and function. *Behavior and Brain Sciences* 9(1).
- [2] Feldman, J. A., and Ballard, D. H. (1982) Connectionist models and their properties. *Cognitive Science* 6, pp. 205-254.
- [3] Hinton, G. E., McClelland, J. L., and Rumelhart, D. E. (1986) Distributed representations. In D. E. Rumelhart and J. L. McClelland (eds.), *Parallel Distributed Processing: Explorations in the Microstructure of Cognition*, volume 1. Cambridge, MA: MIT Press.
- [4] St. John, M. F. and McClelland, J. L. (1986) Reconstructive memory for sentences: a PDP approach. *Proceedings of the Ohio University Inference Conference*.
- [5] Sullins, J. (1985) Value cell encoding strategies. Technical report TR-165, Computer Science Department, University of Rochester, Rochester, NY.
- [6] Touretzky, D. S., and Hinton, G. E. (1985) Symbols among the neurons: details of a connectionist inference architecture. *Proceedings of IJCAI-85*, Los Angeles, CA, pp. 238-243.
- [7] Touretzky, D. S., and Hinton, G. E. (1986) A distributed connectionist production system. Technical report CMU-CS-86-172, Computer Science Department, Carnegie Mellon University, Pittsburgh, PA.
- [8] Touretzky, D. S. (1986) BoltzCONS: reconciling connectionism with the recursive nature of stacks and trees. *Proceedings of the Eighth Annual Conference of the Cognitive Science Society*, Amherst, MA, pp. 522-530.
- [9] Touretzky, D. S. (1986) Representing and transforming recursive objects in a neural network, or "Trees do grow on Boltzmann machines." *Proceedings of the 1986 IEEE International Conference on Systems, Man, and Cybernetics*, Atlanta, GA, pp. 12-16.




Figure 1: A graph of $\log \alpha$ vs. N for even k values (memory capacity) from 2 to 20. $p = 0.01$.